

CAMA PLATE



CAMA PLATE

The special construction of the panels ensures maximum function. The mix of materials fits: CAMA PLATE consists of aluminium plates with an EPDM inlay at the heart. Aluminium for strength. EPDM for optimal cable support. The cable entry plates are available in all common configurations. Special customer requirements are individually realized with the CAMA PLATE FLEX product range.

Highlights:

- Standard portfolio for common cut out dimensions
- Design wishes can be easily implemented
- Clamping range up to 8 mm
- Pressure-resistant EPDM plate
- Heavy-duty metal plates, stainless steel on request
- Integrated strain relief
- IP 66, customer-specific up to IP 67
- Easy to assemble
- Installation height 5 mm

Spezifikation:

Material:	EPDM / ALU
Fire class:	UL 94-V0, self extinguishing*
Protection class:	IP65 and IP66
Temperature range:	-40°C to +130°C (static)
Height:	5 mm
Product feature:	Halogen- and silicone free
Cut out dimensions:	112 x 36mm or flexible according to customers requirements

IP65

IP66

RoHS compliant

UL 94-V0

Made in EU

Halogen free








Silicon free

UV resistant

FLEX

CAMA PLATE / CAMA FLEX

CAMA PLATE

	Discription	Article No.	Cut out dimensions	Quantity of entries	PU pcs
	PLATE 24/23	2030010	116 X 36 mm	23 23 x 3-6 mm	10
	PLATE 24/13-1	2030011	116 X 36 MM	13 11 x 3-6 mm 2 x 12-19 mm	10
	PLATE 24/13-2	2030012	116 X 36 MM	13 6 x 3-6 mm 4 x 12-19 mm 1 x 9-13 mm 2 x 11-16 mm	10
	PLATE 24/17	2030013	116 X 36 MM	17 10 x 3-6 mm 5 x 5-9 mm 2 x 9-13 mm	10
	PLATE 24/12	2030014	116 X 36 MM	12 4 x 3-6 mm 2 x 5-9 mm 6 x 9-13 mm	10
	PLATE 24/16	2030015	116 X 36 MM	16 10 x 3-6 mm 6 x 5-9 mm	10
	PLATE FLEX	on request			